



STRADA

The Strada decorative film, featuring a pattern of opaque horizontal bands, allows you to effectively customize your windows and glass partitions.



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

TECHNICAL DATA

Data calculated based on film applied to clear glass 3 mm thick (* on double glazing 4-16-4)

Ultraviolet transmission	0%
Visible light transmission	0%
Reflection of external visible light	0%
Reflection of internal visible light	0%
Total solar energy rejected	0%
Total solar energy rejected 2 *	0%
Solar ratio:	
Solar energy reflection	0%
Solar energy absorption	0%
Solar energy transmission	0%
Reduction in Solar Glare	0%
G-value	NC
U-value	NC
Shading coefficient	NC
Installation type	Interior
Roll length	30,5 m
Film composition	PET
Thickness	40 µ
Colour from the outside	Frosted

MAINTENANCE

Use soapy water solution for cleaning. Do not clean for at least a month after installation and do not apply any type of stickers or adhesive on the film. For more information read our maintenance instructions and quality standards on our website, www.solfilm.se

INSTALLATION ADVICE

Vertical installation and on standard glass surface *

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ! Caution ✗ Not

Recommended

** Recommendations provided on the basis of a glazed surface covering up to 2.5 m².*

CONSTRUCTION

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation

